



COPPER



100 MHz cat. 5E

UTP 5E

According to



DX21**-*

- > IEC 61156
- > EN 50288-3
- > IEC 11801 2nd Ed.
- > EN 50173 2nd Ed.
- > EIA/TIA 568 B.2

1st ISSUE 2006

ARCHITECTS OF LIGHT



CONSTRUCTION (NOMINAL VALUES)




cat. 5E

Conductor	annealed copper wire		AWG	24
Insulation	solid polyethylene	diameter	mm	0,93
Outer sheath	PVC or Afumex®	single	diameter	5,3
		siamese	outer dim	5,3x10,7
Weight	single		kg/km	31
	siamese		kg/km	63

ELECTRICAL CHARACTERISTICS AT 20 °C (TYPICAL VALUES)

GRAPH

Operating Voltage	≤	125 Vdc
DC Loop Resistance	≤	170 Ω/km
Capacitance Unbalance	≤	1600 pF/km
Input Impedance		100±15 Ω
NVP @ 100 MHz		0,68 c nominal
Skew @ 100 MHz	≤	15 ns/100 m
LCL	≥	40 dB
RL headroom	>	7 dB
NEXT headroom	>	8 dB
PS-NEXT headroom	>	8 dB
ACR @ 600 MHz	>	25 dB
PS-ELFEXT headroom	>	7 dB



ORDERING CODE

cable	code	sheath	std colour	length	packaging	marking
UTP 4P	DX2105-3	Afumex® LSZH	Violet RAL 4005	m 305	box	PRYSMIAN DX2105 - UTP 4x2x24AWG LSZH - CAT. 5e 200 MHz
UTP 4P	DX2105-5	Afumex® LSZH	Violet RAL 4005	m 500	drum	ISO/IEC 11801 - EN 50173 - EIA/TIA 568.B.2 - SGS CERTIFIED
UTP 4P	DX2105-1	Afumex® LSZH	Violet RAL 4005	m 1000	drum	YWWY metric m
UTP 4P	DX2100-3	PVC	Grey RAL 7001	m 305	box	PRYSMIAN DX2100 - UTP 4x2x24AWG - CAT. 5e 200 MHz ISO/IEC
UTP 4P	DX2100-5	PVC	Grey RAL 7001	m 500	drum	11801 - EN 50173 - EIA/TIA 568.B.2 - SGS CERTIFIED YWWY
UTP 4P	DX2100-1	PVC	Grey RAL 7001	m 1000	drum	metric m
UTP 2x4P	DX2125-5	Afumex® LSZH	Violet RAL 4005	m 500	drum	PRYSMIAN DX2125 - UTP 2x(4x2x24AWG) LSZH - CAT. 5e 200 MHz ISO/IEC
UTP 2x4P	DX2125-1	Afumex® LSZH	Violet RAL 4005	m 1000	drum	11801 - EN 50173 - EIA/TIA 568.B.2 - SGS CERTIFIED YWWY metric m
UTP 2x4P	DX2120-5	PVC	Grey RAL 7001	m 500	drum	PRYSMIAN DX2120 - UTP 2x(4x2x24AWG) LSZH - CAT. 5e 200 MHz ISO/IEC
UTP 2x4P	DX2120-1	PVC	Grey RAL 7001	m 1000	drum	11801 - EN 50173 - EIA/TIA 568.B.2 - SGS CERTIFIED YWWY metric m

About Us

Prysmian is a global market leader in optical cables, supplying a major part of the world's optical cable needs. With a strong heritage of highly advanced R&D, Prysmian is at the leading edge of the technology.

With a worldwide manufacturing presence in 12 countries and in 4 continents Prysmian's global experience and local manufacturing capacity is a significant force in the international marketplace, assuring continuity of supply and high level of service.

Prysmian's optical technology encompasses optical fibers, cables, connectivity, projects and services ensuring that not only the right cable but the right total optical communication system is matched to our customers' needs.

Prysmian offers a complete service from design planning, manufacture and installation through to technical support of commissioned cable networks. Planning and surveying are the cornerstone of our operation, with quality maintained through the expertise and dedication of all our staff working across the business to ISO 9001 and 14000 standards.

When a project is in Prysmian's hands, our customers can depend on a total quality service.

Specifications are subject to change without notice. Cable are designed and tested according to the main national and international specifications (IEC specifications).

dega design group